

**PVC  
FREE**

**HALOGEN  
FREE**

**PHTHALATES  
FREE**

Our new Green Power flexible magnet is 100% PVC free and is the thinnest, lightest and strongest magnetic sheet of it's kind currently available on the market.

**Make the switch to  
Green Power magnet today.**

[Greenpower@magnetic-solutions-ltd.co.uk](mailto:Greenpower@magnetic-solutions-ltd.co.uk)

Suitable for UV/Sol/Latex printing

Only available from Magnetic Solutions Ltd,  
part of The Sanders Group, Europes largest combined  
supplier of flexible magnetic and ferro materials.

Magnetic Solutions Ltd, Unit 4, Brooklands Business Park,  
Leigh Street, Sheffield, S9 2PR, (+44) 0114 242 2211

# Green Power Magnet

# Green Power Magnet

## Features

- “Green” PVC-free print medium
- Suitable as a graphic system solution
- Digitally printable
- Wide range of application areas

## Applications

- In-store, Outdoor, Automotive & Retail
- Retail & Warehouses
- Exhibitions & Displays
- Trade, Offices & Schools

## Advantages

- Lightweight and easy to transport so more favourable transport costs
- Easy to apply and remove
- Printable with a variety of inks

## Product Specifications

Product	Thickness (mm)	Width (mm)	Length(m)	Holding force	Top layer	Ink compatibility*
GreenPower 2	0.30	1020/1270	20/30	23 gr/cm <sup>2</sup>	PET	UV/Latex/(Eco) Solvent
GreenPower 4	0.50	620/1020/1270	20/30	55 gr/cm <sup>2</sup>	PET	UV/Latex/(Eco) Solvent

## Storage Conditions

- Stored in original packaging
- Shelf life is 12 months at 21 °C and 30% humidity
- Temperature range for end use should be between -20/+70 °C

## Installation/Handling

- GreenPower should be applied to a clean surface
- GreenPower processes best between 10-35 °C and humidity between 30-60%

## Cautions

- Excessive build-up of UV ink should be avoided, soft UV ink is recommended
- Hard UV ink can cause brittleness and cutting problems

GreenPower: recognisable green UV Coating



GreenPower: paper printer run-in = less waste

