



Frontlit Banner PVC 510g

March 2021

Description:	FP-510FR / Frontlit Banner PVC 510g	
Application:	- Banner applications - Trade shows - Rollups	
Compatibility:	- (Eco) Solvent, Latex inks, UV curable	
Packaging:	Packed in strong carton tubes and rolls are wrapped and protected inside the tube.	
Specifications:	- Weight: 510gsm - Core size: 3 inch - Fabric dtex 1100 - Fabric construction warp/weft 7x7cm/18x18inch - PVC g/m² 350 g/m² - Type Coated - Breaking strength warp 2000 N5cm - Breaking strength weft 1800 N5cm - Tearing strength warp 200 N - Tearing strength weft 100 N - Temperature resistance -15°C/+70°C - Fire retardant / REACH compliant	
Available sizes:	Product code	Product size
	- FP-510FR110	914mm x 30m
	- FP-510FR110	1370mm x 30/50m
	- FP-510FR137	1370mm x 30/50m
	- FP-510FR160	1600mm x 30/50m
	- FP-510FR185	1850mm x 50m
	- FP-510FR220	2200mm x 50m
	- FP-510FR250	2500mm x 50m
	- FP-510FR320	3200mm x 50m
Printing guidelines:	Max. temperature (material) should not exceed 80°C as overheating can impair the flatness of the media. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.	
Storage conditions:	1 year under normal conditions (10–25°C at a relative humidity of 30–75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.	
Disposal:	The media and final prints can be disposed as PVC waste. Material is suitable for recycling. Please consult local recycle resources. For treatment of ink or ink residue, please refer to your printer manual or supplier.	
Liability:	Data presented in this product information serve only as a guideline for compatibility and use. Fingerprint Media will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice.	

Fingerprint Media BV
Keizersgracht 555
1017DR Amsterdam
The Netherlands

info@fingerprintmedia.eu